

WESTAG Feuerschutz-Türelemente DIN 4102

Zentral-Leistungstabelle: Hauptfunktion T30 mit möglichen Zusatzfunktionen



Typ															
	40	65	40	65	40	65	40	65	40	65	40	65	68	68	
Türdicke (ca. mm)	40	65	40	65	40	65	40	65	40	65	40	65	68	68	
Feuerschutz (DIN 4102)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Rauchschutz (DIN 18095)	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Schallschutz (DIN 4109)															
SK27	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
SK32	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	○	▷	
SK37	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	○ ¹	○	▷	▷	
Einbruchhemmung ENV 1627															
WK2	○	○													
WK3		○													
Klimaklasse (RAL RG 426, Volltür)															
II	●	●	●	●	●	●	●	●	●	●	●	●			
III	○	○	○	○	○	○	○	○	○	○	○	○			
Türausführung															
gefälzt	●		●		●		●		●		●				
doppelt gefälzt		●		●		●		●		●		●			
stumpfeinschl. gefälzt	○	○	○	○	○	○	○	○	○	○	○	○	●	●	
ungefälzt	○		○		○		○		○		▷				
Türschließer															
OTS	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
BTS	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
ITS		○		○		○		○		○		○	○	○	
Verglasung	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Zargen															
Stahlzarge	●	●	●	●	●	●	●	●	●	●	● ¹	●			
Holzzarge	●	●	●	●	● ¹	●	●	●	●	●	● ¹	●			
Blockrahmen	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Einbausituation															
Massivwand	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Beton	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Leichtbau-															
Metallständerwerk	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Verglasungswand	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

- Standard
- möglich
- ▷ auf Anfrage
- ¹ Türdicke ca. 43 mm

- OTS = Obentürschließer
- BTS = Bodentürschließer
- ITS = verdeckter, innenliegender Türschließer

Bitte fragen Sie wegen des Prüffortschrittes bei uns nach.